

POWER MAX

10W-40



ULTRA
LUBRICANTS

WORLD CLASS LUBRICANTS
FOR TROPICAL CONDITIONS

GENERAL

Ultra PowerMax 4T is a premium quality multi-grade 4-stroke gasoline engine oil developed for the latest high performance air cooled 4-stroke motorcycles. Ultra PowerMax 4T is blended with high quality hydro-treated base oils and unique performance additives to provide superior protection for engine, gearbox and wet clutch used in 4-stroke motorcycles.

Ultra PowerMax 4T exceeds the performance requirements for API Service Categories SL, SJ, SH and SG in fuel economy, oil consumption/emissions system protection, oxidation control and high temperature piston deposits.

Ultra PowerMax 4T is designed with “**Moly Trimer Technology**” to provide optimum protection to the three (3) critical areas of the motorcycle: engine, gears and clutch.

PERFORMANCE SPECIFICATIONS

The **Ultra PowerMax 4T** range of lubricants meets or exceeds the test requirements of:

- API SL
- JASO MA

KEY BENEFITS

The use of **Ultra PowerMax 4T 10W-40** would result in:

- Improved Engine response
- Greater Wear Protection at Start-up
- Unique combination of detergents and dispersants to provide excellent control on piston deposits leading to faster heat dissipation.
- Enhanced lubrication for maximum horsepower.
- Optimized frictional properties eliminate wet clutch slippage resulting in increased power and fuel economy.
- Effective rust and corrosion inhibition property ensures longer life of critical components

MAIN APPLICATIONS

- For use in all 4-stroke engines requiring an oil meeting API SL/SJ/SH/SG standards
- For use in all 4-stroke motorcycles with or without wet clutches including those specifying the use of a JASO MA qualified oil.

TYPICAL PROPERTIES

	TEST METHOD	
SAE Viscosity Grade	J 300	10W40
Kin. Viscosity @ 40°C, cSt	ASTM D445	146.50
Kin. Viscosity @ 100°C, cSt	ASTM D445	13.50
Viscosity Index	ASTM D2270	145
Specific Gravity, 60/60°F	ASTM D1298	0.866
Pour Point, °C	ASTM D97	-30
Flash Point, (PMCC) °C	ASTM D93	224
TBN, mg KOH/g	ASTM D4739	9.0

HEALTH AND SAFETY

Ultra PowerMax 4T 10W-40 is unlikely to pose any health or safety hazards when used in the recommended applications, provided good standards of personal and industrial hygiene are observed. Please refer to the Material Safety Data Sheet (MSDS) for further information.

Revision Date 03/01/22