



FLUSHING Oil

WORLD CLASS LUBRICANTS
FOR TROPICAL CONDITIONS

GENERAL

Ultra Flushing Oils are manufactured from premium quality Group II hydro-treated base oils. They are suitable for general-purpose lubrication where non-additive oils meet the lubrication requirements.

These oils offer the following benefits:

- High thermal stability
- Low carbon forming tendency
- Outstanding oxidative stability
- Improved system cleanliness and new oil life
- Good Demulsibility
- Low Foaming Tendency

MAIN APPLICATIONS

- Used to remove built up system contaminants and provide maximum life for new lubricant fill.

TYPICAL PROPERTIES

	TEST METHOD						
ISO Viscosity Grade	ISO 3448	32	46	68	100	150	220
Kin. Viscosity @ 40°C cSt	ASTM D445	32	46	68	100	150	220
Kin. Viscosity @ 100°C cSt	ASTM D445	5.38	6.72	8.65	11.20	14.60	18.60
Viscosity Index	ASTM D2270	101	98	98	97	96	94
Colour	ASTM D1500	<1.0	<1.0	<1.0	<1.0	<2.0	<2.0
Pour Point°C	ASTM D97	-24	-24	-24	-21	-12	-12
Closed Flash Point °C	ASTM D93	200	204	210	214	218	218
Rust Characteristics, Procedure A,	ASTM D665	Pass	Pass	Pass	Pass	Pass	Pass

HEALTH AND SAFETY

Ultra Flushing Oils is unlikely to pose any health or safety hazards when used in the recommended applications, provided good standards of personal and industrial hygiene are observed. Please refer to Material Safety Data Sheet (MSDS) for further information.