

# Multi-Vehicle ATF

## Full Synthetic Dexron VI



WORLD CLASS LUBRICANTS  
FOR TROPICAL CONDITIONS

### GENERAL

**Ultra Multi-Vehicle ATF Full Synthetic Dexron VI** with “Smooth Drive Technology” represents the latest technology in full synthetic automatic transmission fluids. This ATF is designed for the newest generation of highly efficient transmissions now installed in most vehicles. It is a fuel efficient choice as well for older models, such as those currently using Dexron-III.

**Ultra Multi-Vehicle ATF Full Synthetic Dexron VI** is recommended for use in all GM DEXRON® applications and in transmissions applications calling for Toyota/Lexus/Scion WS, Nissan Matic J and Matic S, Ford part numbers XT-10-QLV and XT-6-QSP, Honda/Acura Z-1 and DW-1, and Hyundai SP-IV. Check owner’s manual for specific recommendations.

This product is not recommended for Ford Type F, Continuously Variable Transmissions (CVT) or Double Clutch Transmissions (DCT).

### PERFORMANCE SPECIFICATIONS:

*Ultra Multi-Vehicle ATF Full Synthetic Dexron VI* has been fully tested and meets the following specifications:

- General Motors Dexron VI
- Ford Mercon LV, SP

### KEY BENEFITS:

- Enhanced friction durability for smooth transmission performance
- Extended fluid life allowing longer drain intervals twice that of Dexron –IIIH
- Low viscosity formula for maximum fuel efficiency
- Maximizes the life of higher mileage transmissions

**Ultra Multi-Vehicle ATF Full Synthetic Dexron VI is suitable for use in:**

Audi/VW G-055-540 (A2)	GM Synthetic ATF
BMW 81 22 9 400 272/275 - DEXRON® II	GM Type A Suffix A
BMW 81 22 9 407 858/859 - DEXRON® III	GM WS-ATF
BMW 83 22 0 397 114 - DEXRON® VI	Honda ATF DW-1, ATF Z1
Ford M-LV, XT-10-QLV	Hyundai NWS-9638 T-5
Ford M-SP, XT-6-QSP	Hyundai/Kia SP-IV/SPH-IV
GM DEXRON® II	JASO M315, Class 1A
GM DEXRON® IID	Toyota/Lexus/Scion WS
GM DEXRON® IIE	Mercedes 236.41
GM DEXRON® IIIG	Mitsubishi DiaQueen ATF-J2, ATF-J3
GM DEXRON® IIIH	Nissan/Infiniti Matic-J, Matic-S

**TYPICAL PROPERTIES:**

	TEST METHOD	
SAE Viscosity Grade	SAE J-300	20
Kin. Viscosity @ 40°C cSt	ASTM D445	31.02
Kin. Viscosity @ 100°C cSt	ASTM D445	6.05
Viscosity Index	ASTM D2270	147
Specific Gravity 60/60°F	ASTM D1298	0.7089
Brookfield Viscosity @ -40°C	ASTM D5393	13,470
Colour		Red
Pour Point °C	ASTM D97	-42
Flash Point, (PMCC) °C	ASTM D93	204

**HEALTH AND SAFETY**

*Ultra Multi-Vehicle ATF Full Synthetic Dexron VI* is unlikely to pose any health or safety hazards when used in the recommended applications, provided good standards of personal and industrial hygiene are observed. Please refer to the Material Safety Data Sheet (MSDS) for further information.

Revision Date 03/01/22