



WORLD CLASS LUBRICANTS
FOR TROPICAL CONDITIONS

Premium

10W30

GENERAL

Ultra Premium 10W30 is a high performance crankcase motor oil meeting the **API Service Category SP** which represents a significant upgrade in engine oil performance over previous categories.

Ultra Premium exceeds the performance requirements for API Service Categories SN, SM, SL, SH, SG and SJ in fuel economy, oil consumption/emissions system protection, oxidation control and high temperature piston deposits.

It is designed to provide protection against low-speed pre-ignition (LSPI), timing chain wear protection, improved high temperature deposit protection for pistons and turbo chargers, and more stringent sludge and varnish control.

KEY BENEFITS

The use of **Ultra Premium** would:

- Protect and extend the life of engine bearings
- Reduce valve train wear and tappet knocking
- Reduce battery drain and ensure faster engine protection at startup
- Increase available engine power and mileage
- Protect and extended the life of your catalytic converter
- Lower piston-zone deposits and the need to de-carbonize head
- Prevent Ring-sticking, reduce engine wear and blow-by
- Protect against engine deposits and metal corrosion
- Reduce oil consumption
- Protection against bore polish
- Maintain the oil viscosity longer

PERFORMANCE SPECIFICATIONS

The **Ultra Premium** range of lubricants meets or exceeds the test requirements of:

- API SP
- ILSAC GF-6A

MAIN APPLICATIONS

- Modern gasoline automobiles in today's marketplace requiring the **API SP** performance rating.
- Earlier passenger cars where API Service Category SP and earlier are recommended.

TYPICAL PROPERTIES

| | TEST METHOD | |
|-----------------------------|-------------|---------------|
| SAE Viscosity Grade | J300 | 10W-30 |
| Kin. Viscosity @ 100°C, cSt | ASTM D445 | 10.70 |
| Kin. Viscosity @ 40°C, cSt | ASTM D445 | 71.45 |
| Viscosity Index | ASTM D2270 | 135 |
| Specific Gravity, 60/60°F | ASTM D1298 | 0.8756 |
| Pour Point, °C | ASTM D97 | -36 |
| Flash Point, (PMCC), °C | ASTM D93 | 210 |
| TBN, mg KOH/g | ASTM D4739 | 6.20 |

HEALTH AND SAFETY

Ultra Premium Motor Oils are unlikely to pose any health or safety hazards when used in the recommended applications, provided good standards of personal and industrial hygiene are observed. Please refer to the Material Safety Data Sheet for further information.

Revision Date: 03/01/22



ULTRA